

# SIGN MOUNTING METHODS

*Choose the mounting method best suited for your specific sign material and mounting surface.*

## ADHESIVE TAPE

Remove the adhesive tape backing. Using a level to ensure the sign is straight, press the sign firmly to the wall.

## SCREW MOUNTING


Using a level to ensure the sign is straight, mark the wall through the screw holes. Drill holes and then insert anchors into the wall. Holding sign in place, fasten screws into wall anchors.

For signs with frames and screw holes, first remove the sign face. Next, position the frame on the wall, and follow the above instructions. Then replace the sign face.

## SILICONE ADHESIVE

For heavy signs, exterior signs, or when applying to textured wall surfaces, it is recommended to use a silicone construction adhesive\* in addition to the adhesive tape on the back of the sign. Apply silicone adhesive as illustrated and remove the adhesive tape backing. Using a level to ensure the sign is straight, press the sign firmly to the wall.

\*Silicone sealant is different from silicone adhesive. Please be sure to use a silicone adhesive to guarantee proper adhesion.



*When installing signs requiring silicone adhesive, be sure to read and follow the manufacturer's instructions.*

**Before starting, verify the wall surface is smooth and free of any dirt or dust. Complete any wall treatments, such as wallpapering or painting, prior to sign installation.**